

醋酸布單面膠帶系列 (黑色/白色)

Acetate Cloth Single-Sided Tape Series (Black/White)

Item	RK-AC 100120 (B)	RK-AC 170200 (B)	RK-AC 180200
總厚 (mm) Total thickness	0.12	0.20	0.20
規格 Size	1200*30M/50M/100M	1080*50M/100M(T0.20) ; 1190*50M/100M(T0.20)	
基材厚 Substrate thickness	0.10	0.17	0.18
膠水 Adhesive	亞克力 Acrylic		
膠帶顏色 color	膠面黑色 Black		
管芯 Tube core	3.0" (76.0)		
離型紙/膜 Release Paper/film	LOGO 或無 LOGO的離型紙(T0.10 白紙/黃紙);或無紙 LOGO or no LOGO white paper(T0.10 white paper, T0.10 yellow paper)or NO Release Paper		
180 度剝離力 : 304 鏡面不銹鋼板 (Kg /1 inch 0.5H RT) Adhesion to Stainless steel 標準 standard : GB/T 2792-2014/ASTM-D3330	≥ 1.2	≥ 1.5	≥ 1.5
180 度剝離力 : 鋁板 (Kg /1 inch 72H RT) Adhesion to Al foil	≥ 1.2	≥ 1.5	≥ 1.5
初粘性(球號) Viscous force 標準 standard : GB/T4852-2002	≥ 1#	≥ 1#	≥ 1#
常溫保持力 (1 inch) hear Strength – ASTM D3654 1000grams at 72 ° F (22°C) 標準 standard : GB/T4851-1998	≥ 4H	≥ 6H	≥ 6H
延伸率 Elongation	≤ 12%		
拉伸強度 tensile strength (Kg /1 inch)	≥ 5.5		
耐壓 Breakdown voltage	3.0KV,2 mA/5S		
耐溫 Temperature resistance	長期 : Long Term (days, weeks) 80°C 短期 : Short Term (minutes, hours) 120°C		
保質期 Shelf life	Form 12 months from date of manufacture when stored in original cartons at 10-25 °C and 30-70% relative humidity. 原封包裝 12 個月 · 在溫度為 10-25°C、30-70%RH 貯存條件下。		

